MATERIAL SAFETY DATA SHEET

L1 57 Rec 8/86

FOR COATINGS, RESINS AND RELATED MATERIALS

[Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20]

12/20/02					<u> </u>	
Section I						
MANUFACTURERS NAME CONVENIENCE PRODUCTS, INC.	•					
STREET ADDRESS 4205 Forest Park Boulevard	CITY, STATE, AND ZIP	CODE St.	Louis, MO	63108		
	·		ŕ			
EMERGENCY TELEPHONE NO. 314-535-6226						
PRODUCT CLASS Latex Caulk	coduct class Latex Caulk MANUFACTURERS CODE IDENTIFICATION PX-8341-A					
TRADENAME Touch 'n Caulk ; Tub 'n Tile						
Section II — H	AZARDOUS	INGREDIE	NTS			
INGREDIENT	PERCENT	TLV PPM mg/m³		LEL	VAPOR PRESSURE	
						
Aqueous Acrylic Emulsion	30-60%	N.E.		N.A.		
Petroleum Solvent	1-10%	100	_	0.9%	(10 mm Hg @	
)					20°C	
) 	
				-		
Section i	III — PHYSICA	AL DATA			<u> </u>	
BOILING RANGE 2120F	VAPOR DE		HEAVIER.	LIGHTER	THAN AIR	
EVAPORATION RATE FASTER X SLOWER, THAN ETHER					lbs/gal	
Section IV — FIRE	AND EXPLOS	SION HAZ	ARD DATA			
Palstic Liquid, n.o.s.	FLASH PO	INT N.A.			LEL N.A.	
EXTINGUISHING MEDIA Dry chemical, carbon di	.oxide					
UNUSUAL FIRE AND EXPLÓSION HÁZARDS					. " V	

iquid caulk will not burn. The dried film will support combustion.

PECIAL FIRE FIGHTING PROCEDURES

Cover - Offere - Welling				
Section V — HEALTH HAZARD DATA				
THRESHOLD LIMIT VALUE N.A. EFFECTS OF OVEREXPOSURE				
Eye contact may cause irritation. Prolonged or repeated skin contact may cause irritation. Overexposure to vapors in an enclosed area can cause headaches.				
EMERGENCY AND FIRST AID PROCEDURES				
Flush eyes with large amounts of water for at least 15 minutes and consult a physician. Wash skin with soap and water. If swallowed, give 2 glasses of water and induce vomiting.				
Section VI — REACTIVITY DATA				
STABILITY UNSTABLE STABLE CONDITIONS TO AVOID INCOMPATABILITY (Materials to avoid) HAZARDOUS DECOMPOSITION PRODUCTS				
CO, CO ₂ , hydrogen cyanide HAZARDOUS POLYMERIZATION MAY OCCUR CONDITIONS TO AVOID	<u>.</u>			
Section VII — SPILL OR LEAK PROCEDURES				
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Contain the spill and scoop into containers for disposal.				
WASTE DISPOSAL METHOD Disposal of according to federal, state and local regulations.	Jan			
Section V!!! - SPECIAL PROTECTION INFORMATION				
RESPIRATORY PROTECTION				
None normally needed.				
VENTILATION				
Good room ventilation. In an enclosed area, use mechanical or local exhaust to prevent an accumulation of vapors.				

PROTECTIVE GLOVES Rubber gloves. Safety glasses.

OTHER PROTECTIVE EQUIPMENT

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Convenience Products, Inc. makes no warranty with respect thereto and disclaims any liability from reliance thereon.